



	Type	Open	Open with ATS	Silent	Silent with ATS
Generator set	Genset Model	K30250	K30250A	K30250S	K30250SA
	Prime Power Rating	31.3KVA/25KW			
	Standby Power Rating	34.4KVA/27.5KW			
	Size(mm)	1700*700*950		2250*980*1250	
	Weight(KG)	690		856	
	Internal protection	IP22			
	Rate current(A)	45			
	Specific Fuel Consumption(G/KW.H)@100 % Load	≤237			
	Noise at 7 meters away(dB)	N/A		75db	
	Engine	Model	CHINESE Yangdong Y4100G		
NO. of Cylinder		4			
Cylinder Type		V			
RPM		1500			
Bore (mm)		100			
Stroke(mm)		105			
Speed Governor		electronic			
Start system(VDC)		12			
Lub Oil Specification		15W40			
Displacement(Ltrs)		3.298			
Air inspiration		Natural			
Phase		3			
Alternator		Brand	KUSING		
	Model	S184G25D10			
	3 Phase Voltage(1 Phase) Volts	380-415(220-240)			
	RPM/Frequency	1500rpm/50hz			
	Power Factor(%)	0.8(lagging)			
	Voltage Tolerance(+/- %)	1			
	Insulation Class	H			
Control Panel	Brand	KUSING			
	Model	AD6122			
Fuel Tank	Capacity(Ltrs)	Ssupport 8 to 10 hours running time			