



Generator set	Type	Open	Open with ATS	Silent	Silent with ATS
	Genset Model	K30600	K30600A	K30600S	K30600SA
	Prime Power Rating	75KVA/60KW			
	Standby Power Rating	82.5KVA/66KW			
	Size(mm)	1960*800*1000		2600*1100*1450	
	Weight(KG)	986		1585	
	Internal protection	IP22			
	Rate current(A)	108			
	Specific Fuel Consumption(G/KW.H)@100 % Load	≤230			
	Noise at 7 meters away(dB)	N/A		75db	
Engine	Model	YTO LR4B3Z-D92F			
	NO. of Cylinder	4			
	Cylinder Type	L			
	RPM	1500			
	Bore (mm)	108			
	Stroke(mm)	125			
	Speed Governor	electronic			
	Start system(VDC)	24			
	Lub Oil Specification	15W40			
	Displacement(Ltrs)	4.58			
	Air inspiration	turbo			
	Phase	3			
Alternator	Brand	KUSING			
	Model	S224G64D8			
	3 Phase Voltage(1 Phase) Volts	380-415(220-240)			
	RPM/Frequency	1500rpm/50hz			
	Power Factor(%)	0.8(lagging)			
	Voltage Tolerance(+/- %)	1			
	Insulation Class	H			
Control Panel	Brand	KUSING			
	Model	AD6132			
Fuel Tank	Capacity(Ltrs)	SUPPORT TO RUN 8-10 HOURS			